



## NTN Bearing de Mexico, S.A.



PB 5/8 Bearing 2D drawings and 3D CAD models

0.625 Inch | 15.875 Millimeter x 0 Inch | 0  
 Millimeter x 0.875 Inch | 22.225 Millimeter  
 TIMKEN PB 5/8 Pillow Block Bearings

Bearing No. PB 5/8

|                           |   |
|---------------------------|---|
| Category                  | Pillow Block Bearings   |
| Inventory                 | 4.0   |
| Manufacturer Name         | TIMKEN  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 0.2   |
| EAN                       | 0087796056428   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Eccentric Collar  |
| Housing Style             | 2 Bolt Pillow Block   |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Zinc Coated Stamped Steel   |
| Expansion / Non-expansion | Non-expansion   |
| Relubricatable            | No  |
| Insert Part Number        | RA010RRB  |
| Seals                     | Double Land Riding<br>Rubber Contact  |
| Housing Configuration     | 2 Piece Split   |
| Inch - Metric             | Inch  |
| Other Features            | Single Row   Spherical  <br>Light Duty   With Set Screw   |
| Long Description          | 2 Bolt Pillow Block; 5/8"<br>Bore; 7/8" Base to Center<br>Height; Eccentric Collar<br>Mount; Ball Bearing;<br>2-3/16" Minimum Bolt<br>Spacing; 3-3/16" Bolt |



## NTN Bearing de Mexico, S.A.

|                               |   |
|-------------------------------|---|
|                               | Spacing Maximum; No Relubricatable; Zin                   |
| Category                      | Pillow Block  |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.40   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer URL              | <a href="http://www.timken.com">http://www.timken.com</a> |
| Manufacturer Item Number      | PB 5/8  |
| Weight / LBS                  | 0.44  |
| B                             | 0.875 Inch   22.225 Millimeter                            |
| Nominal Bolt Center to Center | 2.7 Inch   68 Millimeter                                  |
| Actual Bolt Center to Center  | 0 Inch   0 Millimeter                                     |
| D                             | 0 Inch   0 Millimeter                                     |
| Bolt Spacing Minimum          | 2.188 Inch   55.575 Millimeter                            |
| Bolt Spacing Maximum          | 3.188 Inch   80.975 Millimeter                            |
| d                             | 0.625 Inch   15.875 Millimeter                            |